

P12

Measuring 432mm wide x 531mm high x 317mm deep and weighing 20Kg, the P12 can be deployed in vertical or horizontal (wedge monitor) configurations, with HF directivity set to match the specific application. P12 features Active/Passive switching with cabinets available in mobile and installation versions.



P12 cab in main (vertical) and wedge (horizontal) configurations

Specifications

P12 with NEXO electronics	
Frequency Response (+6 dB)	60 Hz - 20 kHz
Peak SPL Level (1m)	138dB Peak (Passive mode) / 140dB Peak (Active mode)
Operating Voltage	55Vrms (150Vpeak)
HF Dispersion (according to horns)	60°x60° - 90°x40° - Asymmetrical Dispersion 60° to 100°x40°
Crossover Frequency	60 Hz - 85 Hz
Nominal Impedance	Active mode (8Ω LF, 8Ω HF) – Passive mode: 8Ω
Product Features	
Components	LF: 1x12" - 8Ω; HF : 1x3" - 8Ω - Neodymium driver
Material	Baltic birch / Poplar plywood
Finish	Black or white structural paint
Front Finish	Steel front grille + Back mesh
Fittings	Handle on both sides Threated inserts on the back and on both sides for connection of mounting accessories Stand fitting on both sides (35mm / 1"3/8)
Connector	4x NL4, 4 poles connectors; 2 on the back and 1 on both sides
Weight	20 kg / 44 lb
Height x Width x Depth	531mm x 432mm x 317mm (20.9" x 17" x 12.4")

L15

Measuring 650mm wide x 430mm high x 550mm deep and weighing 34Kg, the L15 sub employs a 15" long excursion driver in Baltic birch / poplar plywood cabinet with threaded inserts for mounting accessories and an M20 stand fitting.




L15 sub

Specifications


L15 with NEXO electronics	
Frequency Response (+6 dB)	40 Hz - 120 Hz
Peak SPL Level (1m)	139 dB Peak
Operating Voltage	55Vrms (150Vpeak)
Crossover Frequency	85 Hz - 120 Hz
Nominal Impedance	4Ω
Product Features	
Components	1x 15" – 4 ohms – Long excursion – Neodymium driver
Material	Baltic birch / Poplar plywood
Finish	Black or white structural paint
Front Finish	Steel front grille
Fittings	Handles on both sides Threated inserts on both sides for connection of mounting accessories Stand fitting M20
Connector	2x NL4, 4 poles connectors
Weight	34 kg / 75 lb
Height x Width x Depth	430mm x 650mm x 550mm (16.9" x 25.5" x 21.6")

P12/L15 System Accessories


A full range of accessories is available for varying P12 HF directivity and for deploying P12/L15 in mobile and fixed applications.




PNT-P12HORN9040
HORN Dispersion Adapter. 90° - 40°




PNT-P12HORNPS
HORN Dispersion Adapter. PS




PNT-BUMP
LiftBar for P12, use with P12, WMADAPT




PNT-PLADAPT
Pole Stand Adapter, use with P12, HBRK12, VBRK12



PNI-CLADAPT
Ceiling Adapter, use with HBRK12/VBRK12




PNT-VBRK12
Vertical Cradle, use with CLADAPT, PLADAPT




PNI-WM330
Wallmount L Bar for P12, with WMADAPT




PNT-WMADAPT
Wall Mount Adapter for PLUS series




PNT-HBRK12
Horizontal Cradle, use with CLADAPT, PLADAPT



LNT-WB15
Wheelboard for L15



LNT-HBRK15
Horizontal Cradle for L15



LNT-2CASE15
Flight case for 2x L15